

Technical Data Sheet

Benzoflex™ 354 Plasticizer

Applications

- Automotive
- Flexible pvc compounds
- Graphic arts
- Vinyl plastisols

Product Description

Benzoflex™ 354 is a high solvating, non-phthalate plasticizer compatible with a wide range of synthetic resinous materials, and it imparts a softening and flexibilizing effect to these resins. Benzoflex™ 354 is suggested for use as a resin plasticizer/modifier in the formulation of specialty coatings and adhesives and PVC plastisols.

Typical Properties

Property	Typical Value, Units
General	
Acidity (wt%)	0.1 max.
Color Pt-Co	125
Refractive Index @ 25°C	1.53
Specific Gravity @ 20°C/20°C	1.08
Boiling Point	>572 °F (>300 °C)
Flash Point Setaflash Closed Cup	387 °F (197 °C)
Freezing Point	10 °F (-12 °C)
Vapor Pressure @ 20°C	<0.00001 torr (<0.0013 Pa)
Viscosity @ 25°C	634 cP (634 mPa·s)
Wt/Vol @ 20°C	9.01 lb/gal (1.08 kg/L)

Comments

Properties reported here are typical of average lots. Eastman makes no representation that the material in any particular shipment will conform exactly to the values given.

Eastman and its marketing affiliates shall not be responsible for the use of this information, or of any product, method, or apparatus mentioned, and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and for the health and safety of your employees and purchasers of your products. No warranty is made of the merchantability of fitness of any product, and nothing herein waives any of the Seller's conditions of sale.

